



TK-240 XT

Ultra Compact Mobile Fuel Polishing System

The TK-240 Mobile Fuel Polishing System is designed to efficiently and safely clean and restore fuel to pristine condition. The TK-240 incorporates a multi-stage filtration process that reconditions, stabilizes, and decontaminates diesel and biofuels. The TK-240 system is specifically designed for tanks with contaminated fuel that require the removal of water, sediment and sludge accumulation. The TK-240 ultra-compact design is ideal for use on small tanks with limited access ports.



TK-240 XT SPECIFICATIONS

Flow Rate	4 GPM/240 GPH (15.1 LPM/908.5 LPH)
T-Strainer	50 Mesh
Secondary Filter	3 μ Water Block, or 10 μ Fine Filter
Fuel Conditioner	LG-X 500 Inline Conditioner
Pump	Gear Pump
Power	12V 10A
Port Size	1/2" In 1/2" Out
Clear Suction Hose	1/2", 15 ft (4.6 m)
Discharge Hose	1/2", 15 ft (4.6 m)
Dimensions	13" x 12" x 12" (H x W x D) (33 x 30 x 30 cm)
Weight	≈ 26 lbs (11.8 kg)
Not for use with fluids that have a flash point below 100°F (37.8°C).	

TK SERIES FEATURE:

- Compact Industrial Lightweight Design
- Quick Connect Power Connection
- Spill Containment Tray
- Convenient Carrying handle

TK Systems are designed around a self-priming 240 GPH nickel-plated brass gear pump. Quality filtration components are connected using corrosion-resistant stainless steel plumbing. A pressure gauge is installed on the filter housing to ensure optimal filter usage by showing remaining filter life. Available filter elements include stainless steel screens, particulate and water block elements.



1.239.690.9589
1.877.425.4239 Toll Free
www.AXI-International.com

AXI.International

AXInternational

AXIFuel


AXIFuel

REV02030240011217



TK-240 XT

Ultra Compact Mobile Fuel Polishing System



1. Inlet Port
2. Inline Mesh Strainer
3. Nickel-plated Brass Gear Pump
4. LG-X 500 Fuel Conditioner
5. Pressure Gauge
6. Water Block Cartridge
7. Discharge Port
8. Spill Containment Tray

TK-240 XT OPTIONS:

- AC to DC Universal Power Converter (110 to 220V, 50 to 60 Hz Input-12V DC Output)
- 10 μ Fine Filter
- 3 μ Water Block Filter

REPLACEMENT FILTER OPTIONS:

Fine Filter	Part No.	Waterblock Filter	Part No.
10 μ Filter Element	FFS-10	3 μ Water Block Filter	WBS-3

AFC 705/710 FUEL ADDITIVE:

A unique and powerful broad spectrum concentrate for use in diesel, gasoline, bio-fuel, kerosene, and HFO. Benefits include:

- Extended Engine Life
- Extended Filter Life
- Removes / Prevents Carbon Build Up
- Prevents Corrosion
- Cleans Injection System
- Tier 4 Compliant (710 only)
- Stabilized Fuel up to 12 mo.
- Added Lubricity
- Improved Combustion
- Lower Emissions
- Improved Fuel Economy



1.239.690.9589
1.877.425.4239 Toll Free
www.AXI-International.com

AXI.International

AXInternational

AXIFuel

AXIFuel

REV02030240011217